

# ANTI-POSTER COATING 1C

Permanent, transparent coating with extreme anti-poster properties.



## Product description

Anti-Poster Coating 1C is a transparent, 1-component coating based on special silicone technology.

Anti-Poster Coating 1C forms a durable protective layer with extreme anti-poster properties. The coating offers excellent protection against external elements such as rain, sun and extreme temperatures.

Anti-Poster Coating 1C intensifies the colour of the substrate and gives a so-called wet-look effect.

## Use

Anti-Poster Coating 1C is directly applicable on almost all porous mineral substrates. Common applications are concrete, masonry, metal surfaces and wooden surfaces.

## Characteristics

- Posters and stickers release themselves from the surface or are easily removed
- Also offers excellent anti-graffiti properties
- Vapor permeable
- High UV-resistance
- Outstanding outdoor durability

## Technical data

Smell:	Characteristic
Colour:	Transparent
Specific weight:	0,98 kg/L
Flashpoint:	54 °C
Solid content:	>90%
Dilution:	Max 30% with white spirit

## Application conditions

Ambient temperature:	maximum 35°C, minimum 8°C
Substrate temperature:	maximum 35°C, minimum 8°C
Relative humidity:	max 85% and 3 °C above dew point

## Instructions

1. Clean the surface and remove graffiti and any other fouling such as soot, wax, oil, paint residues etc.
2. Make sure the surface is completely dry and dust free.
3. Anti-Poster Coating 1C can be diluted up to 30% with white spirit.
4. Apply by roller, brush or airless sprayer. Apply with an average consumption of 150 to 250 g/m<sup>2</sup> depending on the roughness of the substrate.

## Drying

Water resistant:	after 4 hours (at 20°C)
Cured:	up to 24 hours depending on layer thickness
Fully cured:	approx. 7 days

## Packaging

1 and 5 kg

## Consumption

Consumption is 4-8 m<sup>2</sup> per liter depending on the porosity of the surface.

## Practical information

- Empty packaging completely after opening. After exposure to air, any remaining product will continue to harden and thicken.
- Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition.
- Clean tools with white spirit immediately after use. Cured material can only be removed mechanically.
- For application with airless sprayers please contact one of our technical advisors.

## Storage

Can be kept for at least 12 months in original unopened packaging. Store in a cool, frost-free place.

## Health and safety

Flammable liquid and vapor. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. If in doubt, always consult the safety data sheet or our R&D department



## Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Valeton 15, 5301 LW Zaltbommel  
T. +31 418 680 680  
E. [info@mavro-int.com](mailto:info@mavro-int.com)  
W. [www.mavro-int.com](http://www.mavro-int.com)

## Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: April 2021  
All previous editions become invalid upon this publication

Product code: 57664