

Declaration of Compliance

Business Operator Vikan A/S

Rævevej 1 DK-7800 Skive (+45) 96 14 26 00

Product name 3 Spare part rubber bands for 1011x & 1013x, Purple

Item Number 10028

Plastic Material Thermoplastic elastomer (TPE), 98 %

EU Compliance

Regulation (EC) No 1935/2004 In accordance with EU Commission Regulation no. 1935/2004 article 3, 11(5), 15 and 17

the product is intended for food contact. The product is marked with the "glass & fork"

symbol on the packaging or on the product itself through moulding.

Si

AP(89)1 All pigments in the masterbatch comply with resolution AP 89(1)

Regulation (EC) No 2023/2006 The product is produced according to EU Commission Regulation no. 2023/2006 of 22.

December 2006 on good manufacturing practices for materials and articles intended to

come into contact with food (GMP).

Regulation (EU) No 10/2011 Monomers and intentionally added additives used to manufacture this product are listed

in Annex I of Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Subsequent

amendments up to (EU) 2025/351 are included.

Monomers and/or additives with specific migration limit (SML) are used. The substances with a SML will not migrate in quantities that will exceed the SML, under the specified

conditions of use. Upon request we will supply relevant information regarding these

substances on a confidential basis.

Vikan A/S does not use multi-layer materials or articles with a functional barrier.

Regulations (EC) No 1333/2008 and (EC) No 1334/2008

This material contains intentionally added "dual use" additives for which restrictions or purity criteria are in place in accordance with Regulations (EC) 1333/2008 and (EC) 1334/2008. Upon request we will supply relevant information regarding these substances

on a confidential basis.



US FDA Compliance All raw materials in this product are in compliance with FDA (Food and Drug

Administration in the USA) 21 CFR parts 170 to 199.

The polymers and additives complies with FDA 21 CFR part 174, 175, 176, 177, 178, 181, 182, 184, or 186. Additives are cleared according to FDA 21 CFR Part 178 (Indirect food additives), are generally recognised as safe (GRAS), are prior-sanctioned food ingredients, or are cleared on basis of regulations for food additives of before 1958.

UK Compliance The product complies with The Materials and Articles in Contact with Food (Amendment)

(EU Exit) Regulations 2019 No. 704

Danish Compliance The product complies with the Danish consolidation Act no. 681 of 25/05/2020.

Japanese Compliance All substances (polymers, monomers and additives) used in Vikan products comply with

Article 18(3) of the Japanese Food Sanitation Act and are listed in Tables 1 and 2 of

Appendix 1 of the Positive List.

Migration analysis plastics Samples of the product, or a similar product made from identical plastic material, have

been tested for overall migration according to the test conditions specified in (EU) 10/2011 for repeated use, and the article comply with the overall migration limit of 10

mg/dm² or 60 mg/kg.

Test conditions for overall migration were OM0 (30 min at 40 °C)

Food simulants used for overall migration were 50 % ethanol (simulant D1) and 3 %

acetic acid (simulant B).

Compliance with specific migration limits, and other restrictions, has been documented

through testing, calculation or simulation.

Max ratio of food contact surface

area to volume

2.1 dm²/100 ml

Food contact types The product is suitable for contact with the following types of food under the intended and

foreseeable conditions of use:

✓ Aqueous

✓ Acidic

✓ Alcoholic

✓ Dry

Food contact usage time and

temperature

Any food contact conditions up to 40 °C for 30 min.

Non-food contact usage temperature

Minimum temperature: Maximum temperature: 80 °C

 Vikan A/S
 Rævevej 1
 P (+45) 9614 2600
 vikan@vikan.com

 CVR. 10290147
 DK-7800 Skive
 F (+45) 9614 2655
 www.vikan.com



General

Equipment should be cleaned, disinfected and sterilised, as appropriate to it's intended use, before use.

It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.

Recommended sterilisation temperature (Autoclave): 121 °C

We will make the relevant background documentation available to the competent authorities, at their request.

Vikan A/S is registered with the Danish Veterinary and Food Administration (DVFA), and our mandatory Own Control System is subject to inspection by the DVFA.

Date

Made By

7/1/2025

Marta Sztuka

M. Scholie

Materials and Compliance Specialist